

RRKL/RS-RM/LP/11/17

w.e.f. 7th NOVEMBER, 2017

LIST PRICE
RATNAFLEX - SINGLE / MULTICORE CABLES

PVC Insulated unsheathed Single Core & PVC round sheathed Multicore bright Electrolytic annealed bare copper conductor Flexible Industrial Power Cables for working voltages upto and including 1100 Volts, as per IS 694 : 2010 (HSN CODE : 8544)

SIZE SQ. MM	CONFIG.	AMPS	(Rate per 100 meter)			
			SINGLE CORE	2 CORE	3 CORE	4 CORE
0.5	16/0.2	5	571	1772	2305	2902
0.75	24/0.2	8	822	2340	3123	4053
1.0	32/0.2	13	1057	2755	3772	4828
1.5	30/0.25	17	1498	3751	5272	6931
2.5	50/0.25	24	2468	6025	8504	11060
4.0	56/0.3	30	3854	9324	13084	17239
6.0	84/0.3	38	5737	13356	19302	25404
10.0	140/0.3	52	9777	23777	34249	44987
16.0	126/0.4	70	15819	37272	53797	71058
25.0	196/0.4	88	25169	59930	86638	114433
35.0	276/0.4	112	35207	-	121566	160727
50.0	396/0.4	146	49732	-	172710	227668
70.0	360/0.5	216	70809	-	255272	337762
95.0	480/0.5	262	94813	-	339066	448868
120.0	608/0.5	310	119800	-	428055	566572
150.0	750/0.5	355	148507	-	-	-
185.0	931/0.5	415	182366	-	-	-
240.0	1200/0.5	500	237612	-	-	-
300.0	1500/0.5	550	296635	-	-	-

PVC Insulated unsheathed Single Core & PVC round sheathed Multicore bright Electrolytic annealed bare copper conductor Flexible Industrial Power Cables for working voltages upto and including 1100 Volts. (HSN CODE : 8544)

400.0	2013/0.5	590	410989	-	-	-
500.0	2562/0.5	660	522493	-	-	-
630.0	3416/0.5	725	694547	-	-	-

PVC Insulated & PVC round sheathed Multicore bright Electrolytic annealed bare copper conductor Flexible Industrial Control Cables (RATNAFLEX JZ-500), Voltages Grade 300/500 V. (HSN CODE : 8544)

SIZE SQ. MM	CONFIG.	AMPS	5	6	7	8	10	12	14	16	19	24
			CORE *	CORE *	CORE *	CORE *	CORE *	CORE *	CORE *	CORE *	CORE *	CORE *
0.5	16/0.2	5	4051	4782	5432	6389	8004	9401	10675	12091	14268	18261
0.75	24/0.2	8	5671	6920	7532	9033	11266	13400	15256	17571	21186	26538
1.0	32/0.2	13	7099	8203	9434	10914	14011	16456	19091	21820	26902	33110
1.5	30/0.25	17	9694	11848	13424	15440	19916	23491	27351	30806	36450	46703
2.5	50/0.25	24	15985	19286	21912	25374	32284	38020	44175	50978	59481	76111
4.0	56/0.3	30	24228	29506	34090	40146	50662	60013	69895	79662	94108	120237
6.0	84/0.3	38	37191	44132	50918	58927	75296	89251	103458	117836	139048	177415
10.0	140/0.3	52	63503	-	-	-	-	-	-	-	-	-
16.0	126/0.4	70	97172	-	-	-	-	-	-	-	-	-

GST : The above prices are exclusive of GST.

Packing : Order should be in Standard packing.

Freight : Value upto Rs.1,50,000/- on 'TO-PAY' basis & above on 'PAID' basis

Loading factor for Different Insulation / Sheath :

FR Insulation	FR Sheath	FR-LSH / HR Insulation	FR-LSH / HR Sheath	LSOH Insulation	LSZH Sheath
5%	5%	10%	10%	35%	25%

The item marked * are non stock items, refer to marketing dept. for delivery schedule, MOQ, packing etc.

As per the international practice which is also adopted by BIS, the size of the conductor is decided by its resistance only. The construction of the conductor mentioned in the price-list are only for guidelines and are as per market convention, It may vary within the prescribed limit of IS:8130-2013, with related classes and tables

Note: This is Revised Price List, hence all previous Price List & Discount will not be considered.
THE PRICES ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE